

METHOD AND APPARATUS FOR SEAMLESS INTEGRATION OF IMAGES
USING A TRANSMISSIVE/REFLECTIVE MIRROR

CROSS-REFERENCE TO RELATED APPLICATION(S)

5 The present application claims the priority of U.S.
Provisional Application No. 60/211,814 entitled "Method and
Apparatus for Seamless Integration of Images Using a
Transmissive/Reflective Mirror" filed June 14, 2000, the
contents of which are fully incorporated by reference
10 herein. Further, the present application contains subject
matter related to the subject matter disclosed in U.S.
Patent Application No. 09/591,555 entitled "Multi-Panel
Video Display" filed June 8, 2000, the contents of which
are fully incorporated by reference herein.

FIELD OF THE INVENTION

The present invention is related to display of a
composite image using multiple image sources, and
particularly to method and apparatus for seamless
20 integration of images using a transmissive/reflective
mirror.

BACKGROUND OF THE INVENTION

Computer users often desire to view video or graphic
25 images that exceed the viewable area of a single monitor.
For example, designers of large systems often use computer
aided design (CAD) tools to generate designs. Many times,
these designs are too detailed or too large to fully
display on a single monitor with the desired high enough
30 resolution. In addition, users often display multiple
computer windows simultaneously. The multiple windows
typically overlay and block one another since the viewable

area of a monitor is generally not large enough to accommodate more than a few computer windows at the same time.

A typical home computer user may become frustrated by the crowding of the desktop screen by multiple computer windows. A professional computer user, e.g., a graphic artist or a CAD designer, in addition, may suffer from inefficiency or low productivity associated with being able to view only a portion of a large image or having to stack and re-stack multiple computer windows.

From an entertainment standpoint, the industry has always sought bigger, brighter, higher quality, more involving display technologies with continuous improvements, for example, from black and white to color, from color television to HDTV, and from 35mm film to Imax.

A larger viewable area, i.e., larger screen real estate, and higher resolution, i.e., more pixels, is thus always desirable and very useful, whether for laying out and viewing a larger portion of video or graphic images at the same time or simply for more involvement in the content. Therefore, it is often desirable to display video or graphic images on a viewable area that is bigger than what is typically available on a single monitor. Arrayed display systems have been used to create a viewable area that is taller and/or wider than what is normally available on a single monitor. A typical arrayed display system includes two or more video display devices that are horizontally and/or vertically adjacent to one another.

An important character is the adjacency or the apparent seamlessness of the transition between image segments. If the adjacent segments are too far apart, the users tend to segregate their use of the system by screen

segments, thus dramatically reducing the potential usefulness of the larger work surface. Thus, a highly desirable quality of an arrayed display system is the minimization of apparent segregation between the array
5 segments.

One method of diminishing this segregation is embodied in multi-projector based display systems. These systems typically include two or more video projectors that are arrayed in an overlapping adjacent format with each
10 projector being fed by one channel of a visual computer or other video source. The result generally includes a composite image that combines the additive size, the additive brightness and the additive resolution of the multiple channel sources and the multiple projectors.

15 An example of this projection technology is described in 'U.S. Patent No. 4,974,073 entitled "Seamless Video Display," U.S. Patent No. 5,136,390 entitled "Adjustable Multiple Image Display Smoothing Method and Apparatus," and U.S. Patent No. 6,115,022 entitled "Method and Apparatus
20 for Adjusting Multiple Projected Raster Images," the contents of all of which are fully incorporated by reference herein.

The use of projector-based display systems may provide a larger viewable area and higher resolution than a single
25 monitor or a display device. However, projector-based display systems are not always suited for widespread use by individuals since the current systems can be expensive, large and technically complex.

Multiple conventional computer monitors or flat panel
30 displays may be placed side by side to provide a type of arrayed display system. However, due to the packaging of most standard CRTs and other monitors, such a configuration

typically results in wider than acceptable image segregation, also referred to as a mullion, between the displays. This prevents the displays from having an integrated look as illustrated in FIGs. 1A, 1B and 2.

5 FIG. 1A illustrates three conventional monitors 100, 102 and 104 placed side-by-side in an array. FIG. 1B is a top view of the three arrayed monitors 100, 102 and 104 of FIG. 1A. The monitors 100, 102 and 104 have viewable areas 106, 108 and 110, respectively. The viewable areas are
10 smaller than the front surface of the monitors because of the respective housings. A relatively wide gap or mullion, e.g., gap 112 between the viewable areas 108 and 110 of the adjacent monitors 102 and 104, exists between adjacent viewable areas.

15 FIG. 2 illustrates a distracting effect of the mullions between the viewable areas when the three monitors 100, 102 and 104 are used to display a single composite image. The composite image displays the enlarged text "TEST" across all three of the monitors. As shown in the
20 figure, the first T is displayed on monitors 100 and 102 while the second T is displayed on monitors 102 and 104. The relatively large mullions may distract viewers from viewing the text as a single integrated image.

Therefore, there is a need for an arrayed display
25 system that is capable of providing reduced separation between portions of a composite image in adjacent displays as to reduce viewer distraction. The arrayed display system preferably is affordable to a wider range of users and designed to address ergonomic considerations for
30 providing viewer comfort.

SUMMARY OF THE INVENTION

In one embodiment according to the present invention, an integrated display system is provided. The integrated display system comprises a first display, a second display and a transmissive/reflective mirror. The first display has a display area that faces a user. The second display has the display area that faces a generally vertical direction. The transmissive/reflective mirror has a mirror face between the first display and the user. Images from the first display at least partially pass through the mirror face towards the user, and images from the second display are at least partially reflected by the mirror face towards the user, so as to present a composite image comprising the images from the displays to the user.

In another embodiment according to the present invention, is a method of generating a composite image using a transmissive/reflective mirror. A first image is projected towards a user through the transmissive/reflective mirror. A second image is applied at the transmissive/reflective mirror for the second image to be reflected towards the user. The first image and the second image are slightly overlapped and can be soft edge blended like projected images so that the images appear as a seamless composite image to the user.

In yet another embodiment according to the present invention, is a method of generating a composite image using a transmissive/reflective mirror while applying imaging devices small enough to be carried or worn by the user where a first image is seen directly by the user through the mirror and the second image is seen by the user as a reflected image as described in Figure 7. The first

image and the second image appear as a composite image to the user.

In still another embodiment according to the present invention, is a method of generating a composite image using a transmissive/reflective mirror while applying imaging devices small enough to be carried or worn by the user where a first image is seen directly by the user through the mirror and the second image is seen by the user as a reflected image as described in Figure 7. The first image and the second image are slightly overlapped and can be soft edge blended like projected images so that the images appear as a seamless composite image to the user.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is an illustration of three conventional monitors placed next to one another in an exemplary prior art configuration;

FIG. 1B is a top view of the three conventional monitors of FIG. 1A;

FIG. 2 is an illustration of a display of a composite image across three adjacent conventional monitors arranged in a prior art configuration;

FIG. 3A is an illustration of three adjacent conventional monitors in a physically impossible configuration to show the display areas touching one another;

FIG. 3B is a top view of the three adjacent conventional monitors in a physically impossible configuration of FIG. 3A;

FIG. 4 is an illustration of a display of a composite image across the three conventional monitors in a physically impossible configuration of FIG. 3A;

FIG. 5 is a front view of an integrated display system including three monitors and one transmissive/reflective mirror according to an embodiment of the present invention;

FIG. 6 is a view at an angle of the integrated display system of FIG. 5;

FIG. 7 illustrates optical path from the monitors to the viewer of the integrated display system of FIGs. 5 and 6;

FIG. 8 illustrates optical path from the monitors to the viewer of an integrated display system in another embodiment according to the present invention;

FIG. 9 illustrates a front view of an integrated display system showing spatial relationship between the three monitors in an embodiment according to the present invention without showing the transmissive/reflective mirror;

FIG. 10 is a top view of an integrated display system showing spatial relationship between the three monitors in an embodiment according to the present invention without showing the transmissive/reflective mirror;

FIG. 11 is a front view of the transmissive/reflective mirror operating as a display for an integrated display system in an embodiment according to the present invention;

FIG. 12 is a system diagram that illustrates operation of the three monitors to display images from a multi-channel visual computer, a laptop and a video cassette recorder (VCR) in an embodiment according to the present invention;

FIG. 13 is a system diagram that illustrates operation of the three monitors to display images from a multi-channel visual computer, laptop and a VCR using a matrix

switcher in another embodiment according to the present invention;

FIG. 14A is a front view of an integrated display system in an embodiment according to the present invention, in which a composite image is displayed across display areas of three monitors; and

FIG. 14B is a front view of an integrated display system in an embodiment according to the present invention, in which separate images are displayed on each of display areas of three monitors.

DETAILED DESCRIPTION

FIG. 3A is a physically impossible configuration of three adjacent monitors 300, 302 and 304 shown for illustrative purposes only. FIG. 3B is a top view of the three adjacent monitors 300, 302 and 304 of FIG. 3A in physically impossible configuration. Display areas 306, 308 and 310 of the monitors 300, 302 and 304 are illustrated to be touching one another. This configuration is physically impossible because of the packaging surrounding the display areas, e.g., cathode ray tube (CRT) of the monitors or the flat panels. For example, FIG. 3A illustrates that a left edge 312 of the monitor 302 is located within the monitor 300, a right edge 314 of the monitor 300 is located within the monitor 302, a left edge 316 of the monitor 304 is located within the monitor 302 and a right edge 318 of the monitor 302 is located within the monitor 304.

FIG. 4 is an illustration of a composite image "TEST" being displayed on three adjacent monitors 300, 302 and 304 of FIG. 3A, which is illustrated to be in a physically impossible configuration. A portion of the first "T"

appears on a display area 306 of the monitor 300 while another portion of the first "T" appears on a display area 308 of the monitor 302. Due to the display areas, which may also be referred to as viewable areas, being adjacent to one another, there is virtually no separation between two portions of the first "T", and it is relatively non-distracting. This also applies to two portions of the second "T", which appears on display areas 308 and 310 of the monitors 302 and 304, respectively.

FIG. 5 is a front view of an integrated display system including three monitors (or displays) 500, 502, 504 and one transmissive/reflective mirror 506 in an embodiment according to the present invention. The integrated display system may also be referred to as an integrated monitor system. FIG. 6 is a view at an angle of the integrated display system of FIG. 5. In the described embodiment, the monitors 500, 502 and 504 may include a cathode ray tube (CRT). In other embodiments, the monitors 500, 502 and 504 may be based on other technologies, such as other technologies that provide sufficient luminance after applying the transmissive/reflective mirror 506. The monitors 500, 502 and 504 preferably have substantially flat display areas, i.e., flat panels or screens, in one embodiment of the present invention. In other embodiments, the monitors 500, 502 and 504 may have non-flat display areas.

The monitor 500 preferably is oriented to have its display area 501 substantially normal to ground and facing a user (a viewer). In other embodiments, the monitor 500 may have its display area 501 tilted forward towards the user or backward away from the user.

The monitors 502 and 504 have display areas 503 and 505, respectively. The display areas 503 and 505 preferably face a generally upward direction. In the described embodiment, the monitors 502 and 504 are oriented
5 such that the display areas 503 and 505 are angled in a direction towards facing one another. The display areas 503 and 505 may have an angle of, for example, 20 degrees, with respect to one another.

In other embodiments, the angle between the display
10 areas 503 and 505 and ground may be more or less than 20 degrees or even angling outward, or the display areas 503 and 505 may not be angled and may face a substantially straightly upward direction. For example, by angling the two edge monitors in a three monitor system, all three
15 monitors may be seen as being equidistant to the viewer, which is desirable for ergonomic reasons similar to one embodiment of the invention disclosed in U.S. Patent Application No. 09/591,555 entitled "Multi-Panel Video Display," the contents of which have been fully
20 incorporated by reference herein. For another example, when more monitors (e.g., five monitors) are used, by arraying the monitors with angles, an illusion of a miniature curved screen may be presented to the viewer.

The transmissive/reflective mirror 506, which may also
25 be referred to as a beam splitter, preferably includes a 50/50 transmissive/reflective mirror, which passes through approximately 50% of the incident light and reflects approximately 50% of the incident light.

In other embodiments, the ratio between the amount of
30 transmitted light and the amount of reflected light may be more or less than 1. The transmissive/reflective mirror 506 preferably has a mirror face 507, which may also be

referred to as a face of the mirror. The mirror face 507 preferably is at approximately 45 degree angle (angle A of FIG. 6) with respect to ground, extending upward towards the monitors 502 and 504. In other embodiments, the angle
5 the mirror face 507 makes with respect to ground may be more or less than 45 degrees.

Since the transmissive/reflective mirror 506 is between the display area 501 and the user, the user typically views images on the display area 501 through the
10 mirror face 507. At least a portion of light from the display area 501 typically does not pass through the mirror face 507, and thus brightness of the images from the display area 501 is generally reduced when viewed by the user through the mirror face 507. The ratio between the
15 passed-through and non-passed-through portions of light depends on the transmissive/reflective characteristics of the mirror face used.

Since the display areas 503 and 505 face generally upward direction towards the mirror face 507, the user
20 typically views reflections of the images from the display areas 503 and 505 formed on the mirror face 507. At least a portion of light from the display areas 503 and 505 typically passes through the mirror face 507, and thus brightness of the images from the display areas 503 and 505
25 are generally reduced when viewed by the user as reflections on the mirror face 507. The ratio between the passed-through and non-passed-through portions of light depends on the transmissive/reflective characteristics of the mirror face used.

30 The monitors 502 and 504 preferably are oriented so that the top of images on the display areas 503 and 505, respectively, are closer to a user than the bottom of the

images on the display areas 503 and 505. Thus, when the images from the display areas 503 and 505 are reflected by the mirror face 507, the top of the images appears near the top of the mirror face 507 and the bottom of the images appears near the bottom of the mirror face 507. Similar to typical reflections, the images from the display areas 503 and 505 are generally horizontally reversed when reflected on the mirror face 507, and a left edge of each image typically appears as a right edge of a corresponding reflected image, and vice versa.

FIG. 7, for example, illustrates optical path between the image sources and a viewer eye 510 in this embodiment. For illustrative purposes, only one monitor 500 is facing the viewer and only one monitor 502 is facing generally upward direction in FIG. 7. However, it should be noted that any number of monitors may face the viewer and any number of monitors may be facing generally upward direction to create the composite image with any desired size in various different embodiments of the present invention.

A light output 512 from the monitor 500 is applied to the face of the transmissive/reflective mirror 506. A light component 516 passes through the mirror to be viewed by the viewer while a light component 514 is reflected by the mirror 506 away from the viewer eye 510.

A light output 518 from the monitor 502 is applied to the face of the transmissive/reflective mirror 506. A light component 522 is reflected by the mirror to be viewed by the viewer while a light component 520 passes through the mirror 506 in a direction away from the viewer eye 510.

In an exemplary embodiment, the integrated display system may be placed inside a light controlled cabinet, and the transmissive/reflective mirror 506 preferably creates

the appearance of a virtual image plane in which the images appear as a single composite image. The three images preferably appear to be edge matched to one another, creating a seamless (virtual) composite image. The images
5 may appear to be at an angle with respect to one another. For example, when the angle between ground and each of display areas 503 and 505 is approximately 20 degrees, the images may appear to be at an angle of approximately 20 degrees with respect to one another.

10 The integrated display system may also be coupled to a control unit (not shown) for providing inputs and power to the monitors 500, 502, 504, and for controlling the displays on the monitors. The control unit may be used to control display characteristics of all three of the
15 monitors. In other embodiments, a separate control unit may be used to control display for each monitor. The integrated display system may include a control software for display configuration and maintenance. The control software may be commanded to perform control functions from
20 the control unit or any other external device such as an external computer. The control software may be controlled by using an input device such as a keyboard and/or mouse.

The signals feeding the integrated display system may also be passed through an external signal processing device
25 (not shown) in order to modify each signal relative to the other to create a more uniform, geometrically correct and seamless image. The signal processing may include modification of the images (such as with distortion correction circuitry) in order to correct aberration due to
30 mechanical and/or optical misalignment. This correction preferably performs geometric distortion correction to tune

the flaws of the monitors in order to perfectly align the images either for overlap or for adjacency.

The signal processing may also include modification of the images in order to correct image non-uniformity which may include, but not limited to, hot spotting and/or color balancing such as, for example, disclosed in U.S. Patent No. 6,115,022. Further, the signal processing may also include edge blending, such as, for example, disclosed in U.S. Patent Nos. 4,974,073 and 5,136,390, in an embodiment where the images are overlapped.

In combination, the signal processing may be used to control display characteristics of all three of the monitors. In other embodiments, signal processing capabilities may be built into each monitor or into the multi-monitor system. The signal processing capabilities may be implemented using a control software for display configuration and adjustment of parameters. The control software may be commanded to perform control functions from the control unit or any other device such as an external computer. The control software may be controlled by using an input device such as a keyboard and/or mouse or an automated feedback system.

In an exemplary embodiment, the integrated display system may include a port (not shown), such as a universal serial bus (USB) port, an RS-232 port, or any other conventional or non-conventional serial or control port, for communication with an external device such as a computer. The port may be used to perform control functions. The port input and the control software preferably allows for external control of characteristics including but not limited to: screen input selection, automatic input calibration and three screen interactive

color adjustments. A full setup configuration may be stored and be easily accessible and selectable, by, e.g., screen menu selection, a button selection or clicking a mouse button.

5 The monitors may include liquid crystal display (LCD) monitors or they may include any other commonly or not commonly used monitors such as, for example, plasma display monitors, or they can include new technologies such as E-ink, organic liquid crystals or organic transistors. The
10 monitor input signals may be analog such as composite video or red, blue, green, sync, or the inputs may be digital such as Digital Visual Interface (DVI) or the inputs could be optical or other technologies not yet directly anticipated.

15 The integrated display system in an embodiment according to the present invention is capable of selecting from multiple inputs including but not limited to: a main and auxiliary RGB signals for each of the three monitors, composite video signals and/or S-video (Y/C). These inputs
20 allow for use of other devices in addition to a main multi-channel visual computer. Other devices that may provide inputs to the integrated display system may include laptops, VCR, DVD, video conferencing equipment, cable television set top box, as well as closed circuit
25 television and satellite feeds. The user may then be able to select the input feeds or preset combinations of feeds. The integrated display system may also include audio inputs and be coupled to speakers for audiovisual communications.

FIG. 8 illustrates optical path between image sources
30 (monitors) 530, 532 and a viewer eye 540 in another embodiment according to the present invention. FIG 8 is similar to FIG 7 but the reflected image is coming from

above from the monitor 532 facing downward towards a transmissive/reflective mirror 536 as opposed to from the bottom with a monitor facing upward. Of course, in this embodiment as well, multiple monitors may face downward
5 towards the transmissive/reflective mirror 536 and/or multiple monitors may face the viewer through the transmissive/reflective mirror 536.

FIG. 9 is a front view of an integrated display system in an embodiment according to the present invention,
10 including three monitors 500, 502 and 504, illustrating spatial relationship between the monitors without showing a transmissive/reflective mirror. Angles B1 and B2 between ground and display areas (display surfaces) 503 and 505 of the monitors 502 and 504, respectively, are approximately
15 20 degrees in this embodiment. In other embodiments, the angles B1 and B2 may be more or less than approximately 20 degrees. In still other embodiments, the angles B1 and B2 may be approximately zero degrees and the display areas 503 and 505 may be substantially parallel to ground. FIG. 10
20 is a top view of the integrated display system of FIG. 9.

FIG. 11 is an illustration of an integrated image appearing on the mirror face 507 of the transmissive/reflective mirror 506. When the display areas 503 and 505 are at an angle, e.g., approximately 20
25 degrees, with respect to ground as shown in FIG. 9, left and right images of two arrows and of a vehicle and a tree, respectively, may appear to be at an angle with respect to a center image of a man playing tennis. User may perceive that all three of the images are equidistant from his eye
30 point (location of his eyes) when the display areas 503 and 505 are angled appropriately. When the display areas 503 and 505 are parallel to ground, the user typically

perceives that the three adjacent images are displayed on a flat screen.

In one embodiment, the left, center and right images may be overlapped at the adjacent edges as to generate an overlapped region between the left image and the center image and between the center image and the right image. Edge blending technology may be applied to the overlapped images to enhance the seamless appearance of the composite image generated by the three images. Examples of this projection technology is described in U.S. Patent Nos. 4,974,073, 5,136,390 and 6,115,022, all of which have been incorporated by reference herein.

FIG. 12 is an illustration that shows interfaces, in one embodiment of the present invention, between an integrated display system and devices that provide video and graphics to the integrated display system. The integrated display system preferably includes three monitors 500, 502 and 504 and a transmissive/reflective mirror (not shown). The three monitors 500, 502 and 504 preferably are flat screen CRT monitors. In other embodiments, the three monitors 500, 502 and 504 may be other conventional or non-conventional types of monitors including but not limited to: LCD, plasma display and/or DVI-compatible monitors.

A multi-channel visual computer 700 preferably includes three graphic interface cards 702, 704 and 706. The graphic interface cards 702, 704 and 706 preferably provides images 716, 718 and 720 to corresponding monitors 502, 500 and 504, respectively. The multi-channel visual computer 700 may be based on one or more of Unix, Mac-OS, Windows/NT, MS-DOS and Linux operating systems or any other conventional or non-conventional operating system.

The multi-channel visual computer 700 may provide graphics and/or video signals that represent the images 716, 718 and 720 to corresponding input for each of the three monitors 502, 500 and 504 including but not limited to: DVI, Firewire, or other direct digital formats, main and auxiliary RGB inputs, composite video inputs and S-video (Y/C) inputs among others.

In other embodiments, two or three separate computers may be used in place of the multi-channel visual computer 700 to provide graphics and/or video signals to the integrated display system. The images 716, 718 and 720 may be three unrelated images or each of the images may be a portion of a composite image. The graphic images 716, 718 and 720 may also be substantially identical to one another.

An additional image may be provided by a laptop 710 or any other computer or an electronic device capable of providing an image. The laptop 710 preferably provides an image 726 to the monitor 504 of the integrated display system. For example, the image 726 may include a picture of a vehicle and a tree.

Since the integrated display system in this embodiment is typically used to display three image segments, one on each array segment, when the laptop 710 provides the fourth image 726 in addition to the graphic images 716, 718 and 720 from the multi-channel visual computer 700, a switch 714 preferably is used to switch between one of the images from the multi-channel visual computer 700 and the image 726.

For example, the images 720 and 726 preferably are coupled to the switch 714. The switch 714 preferably multiplexes them to provide an image 728 to the monitor 504 of the integrated display system. The image 728 may be the

image 720 or the image 726 based on the selection by the switch 714. The switch 714 may be manually controlled, e.g., through manipulation of a mechanical switch by the user. The switch 714 may also be electronic and controlled manually or controlled automatically, e.g., by a software running in the control unit (not shown). The switch 714 may also be used to provide the image 720 or the image 726 to one or both of the other two monitors 500 and 502 as indicated by dotted arrows on FIG. 12. In other embodiments, the switch 714 may also receive images from one or more other image sources to be selectively provided to one or more of the monitors 500, 502 and 504.

A video cassette recorder (VCR) 708 in one embodiment may provide a graphic image 722 to a switch 712, which preferably is similar to the switch 714. The image 716 from the multi-channel visual computer preferably is also coupled to the switch 712. The switch 712 preferably operates similarly to the switch 714 in that it selects between the images 716 and 722 to provide as an image 724 to the monitor 502 of the integrated display system. The switch 712 may also be used to provide the image 716 or the image 722 to one or both of the other two monitors 500 and 504 as indicated by dotted arrows on FIG. 12. In other embodiments, the switch 712 may also receive images from one or more other image sources to be selectively provided to one or more of the monitors 500, 502 and 504.

A switch 713, which preferably is similar to the switch 714, receives the image 718, and provides to the monitor 500 as an image 719. The switch 713 may also be used to provide the image 718 to one or both of the other two monitors 502 and 504 as indicated by dotted arrows on FIG. 12. In other embodiments, the switch 713 may be

coupled to one or more other image sources to be selectively provided to one or more of the monitors 500, 502 and 504. In other embodiments, some of the image inputs may be provided to one or more monitors directly without going through a switch.

FIG. 13 is a system diagram that illustrates operation of the three monitors 500, 502, 504 to display images from the multi-channel visual computer 700, the laptop 710 and the VCR 708 using a matrix switcher 715 in another embodiment according to the present invention. The configuration of the system of FIG. 13 is similar to that of the system in FIG. 12 except that a single matrix switcher is used instead of multiple switches. The matrix switcher may receive multiple inputs, and provide any of the inputs as any of multiple outputs.

The matrix switcher 715 may receive images 716, 718 and 720 from the multi-channel visual computer 700, the image 722 from the VCR 708 and/or the image 726 from the laptop 710. The matrix switcher 715 is capable of providing any of these image inputs as an image 725 to the monitor 502, as an image 727 to the monitor 500 and/or as an image 729 to the monitor 504. The matrix switcher 715 may also provide the identical image to any two or three of the monitors 500, 502 and 504. In other embodiments, the switcher 715 may receive image inputs from different number of image sources and/or provide outputs to different number of monitors/display devices.

FIG. 14A is a front view of a transmissive/reflective mirror 506 displaying three images 800a, 802a and 804a on a mirror face 507 in one embodiment of the present invention. The mirror face 507 displays the three images 800a, 802a and 804a as a composite image with virtually no seam or

mullion between the images. In one embodiment, all three images that make up the composite image may be provided by the multi-channel visual computer 700 in FIG. 12. For example, the three images may be provided by the three graphic interface cards, 702, 704 and 706, respectively. In other embodiments, each of the three images may be provided by a different computer, multiple DVD players with prepared media, a multi-channel video server, an electronic device that takes a single image source and spreads it out to multiple channels or any other device capable of delivering the image to the screen.

FIG. 14B is a front view of the transmissive/reflective mirror 506 displaying three images 800b, 802b and 804b on the mirror face 507 in one embodiment of the present invention. The image 802b is substantially the same as the image 802a of FIG. 14A. The image 802b (or the image 802a) may be provided by the graphic interface card 704 shown in FIG. 12. The image 800b showing a couple of arrows, however, displays an image that is independent of the composite image. The image 800b, e.g., may be provided by the VCR 708 through the switch 712 shown in FIG. 12.

The image 804b also is independent of the composite image. For example, the image 804b may be that of a vehicle and a tree. The image 804b, e.g., may be provided by the laptop 710 through the switch 714 shown in FIG. 12. In other embodiments, the image 802b may also be independent of the composite image.

In one embodiment of the present invention, active matrix stereographics may be used with the integrated display system in order to create virtual reality (VR) and/or immersive visualization system by providing a realistic hologram type image (e.g., 3-D stereoscopic view)

of the displayed objects on the composite image. For example, slightly different composite images are generated for the right and left eyes, respectively. The viewpoint preferably is slightly shifted right and left as it would be if an object is viewed first with one eye then another.

A synchronizing signal is sent to an infrared transmitter, which broadcasts an infrared synchronizing signal into the viewing area to be received by a pair of electronic shutter glasses with lenses including fast liquid crystal shutters. The synchronizing signal controls the glasses to alternately blank one eye then the other.

In other embodiments, the integrated display system may also include polarized glasses. polarization of light for the images transmitted through or reflected from the transmissive/reflective mirror is sequentially altered and resulting images are viewed by the user through the polarized glasses in order to see a 3-D stereoscopic view of objects displayed on the composite image.

Accordingly, the present invention provides an integrated display system for displaying a high-resolution composite image. Although this invention has been described in certain specific embodiments, many additional modifications and variations would be apparent to those skilled in the art. It is therefore to be understood that this invention may be practiced otherwise than as specifically described. Thus, the present embodiments of the invention should be considered in all respects as illustrative and not restrictive, the scope of the invention to be determined by the appended claims and their equivalents rather than the foregoing description.

For example, in another embodiment, an integrated display system may include two monitors (left and right

monitors) with display areas substantially normal to ground and facing a user, and one monitor (center monitor) with display area facing a generally upward direction. In this embodiment, the user typically views images from the display areas of the left and right monitors through a mirror face of a transmissive/reflective mirror while viewing the reflection of the image from the display area of the center monitor on the mirror face.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
222